

at least one fan positioned to direct air flow toward the at least one heat sink;

one or more covers that connect to the at least one cylinder top; and

a temperature controlling means for regulating the temperature of the at least one cylinder, said controlling means operably attached to the at least one cylinder.

2. (Original) The thermoelectric temperature controlling device of claim 1 wherein the cover connects to the cylinder top and encloses the air space within the cylinder so that moisture is prevented from entering the cylinder.

3. (Original) The thermoelectric temperature controlling device of claim 1 wherein the at least one cylinder is constructed of thermally conductive material.

4. (Original) The thermoelectric temperature controlling device of claim 1 wherein the at least one cylinder is thermally insulated.

5. (Withdrawn) The thermoelectric temperature controlling device of claim 1 further including a container positioning means disposed on at least one wall of the at least one cylinder.

6. (Original) The thermoelectric temperature controlling device of claim 1 further including a means for rotating a container within the at least one cylinder.

7. (Withdrawn) The thermoelectric temperature controlling device of claim 1 further including at least one heat sink operably joined to at least one cylinder.

8. (Withdrawn) The thermoelectric temperature controlling device of claim 7 further including at least one fan positioned to direct air flow toward the at least one heat sink.

9. (Original) The thermoelectric temperature controlling device of claim 1 further including a slanted base positioned under the main body so that the at least one cylinder is situated in a tilted position with respect to the surface that the main body and base rest upon.

10. (Currently Amended) A thermoelectric temperature controlling device that is capable of holding one or more containers storing a substance, comprising:

a main body having one or more cylinders with a closed bottom portion and an open top portion, said top portion sized to allow a container to pass through and fit inside of the cylinder;

at least one heat sink operably joined to at least one cylinder wall;

at least one container positioning means disposed on at least one wall of the at least one cylinder to direct at least one container toward at least one heat sink;

at least one fan positioned to direct air flow toward at least one heat sink; and

a means for regulating the temperature of the one or more cylinders, said regulating means operably connected to the one or more cylinders.

11. (Original) The thermoelectric temperature controlling device of claim 10 wherein the means for regulating comprises a thermoelectric module, a heat sink, a spacer, a land area, and a fan.

12. (Original) The thermoelectric temperature controlling device of claim 10 wherein the cover connects to the cylinder top and encloses the air space within the cylinder so that moisture is prevented from entering the cylinder.

13. (Original) The thermoelectric temperature controlling device of claim 10 wherein the at least one cylinder is constructed of thermally conductive material.

14. (Original) The thermoelectric temperature controlling device of claim 10 wherein the at least one cylinder is thermally insulated.

15. (Withdrawn) The thermoelectric temperature controlling device of claim 10 further including a container positioning means disposed on at least one wall of the at least one cylinder.

16. (Original) The thermoelectric temperature controlling device of claim 10 further including a means for rotating a container within the at least one cylinder.